

NOTIFICATIO of END of LIFE PRODUCT Heat resistant (105 °C) Fiber Unit NF-TH06

May 9, 2024
To whom it may concern,
OPTEX FA Co., Ltd. appreciates and values your business. We are announcing End of Life of the following products:
Product Description
Heat resistant (105 °C) Fiber Unit NF-TH06
*Including special order specifications and derivative products of the above products
Reason for EOL
End of supply of key components
Last Order Acceptance Date
March 31, 2025
Replacement Products
We regret to inform you that there is no alternative products.
*For details, please see attached sheet or contact OPTEX FA.
Thank you very much for your support for OPTEX FA products.
Thank you very mach for your support for Or TEXT A products.
Sincerely, International Department OPTEX FA Co., Ltd.



Comparison table with alternative proposals

Model		Discontinued Products	Alternative Proposal
		NF-TH06	
Туре		Heat resistant (105 °C) Fiber Unit	-
Reflection mode		Through-beam type	-
Ambient temperature		-40 to +105 °C	-
Minimum bending radius		R10 mm	-
Fiber length		1 m Free cut	-
Dimensions (mm)		2.2 25 15 1000 1 SUS e2.5 SUS PC 10.5 1 Light axis angle 2.2 10 15 1000 2.2 10 15 1000 2.2 10 15 SUS PC Light axis angle 2.2 2 10 15 1000 PC 2.5 SUS PC 2.5 S	-
Sensing Distance (mm) D4RF	16 µs	10	-
	70 µs	40	-
	250 µs	60	-
	500 μs	75	-
	1 ms	85	-
	2 ms	120	-
	8 ms	180	-

^{*}For details, please see attached sheet or contact OPTEX FA.